RG Cable 316

TECHNICAL DATA SHEET

XC-SJ316SK-20



Chengdu Ebyte Electronic Technology Co.,Ltd.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000



XC-SJ316SK-20

Structure		
Item	Material	Diameter(mm)
Conductor	Silverplated copper	7/0.17±0.003
Insulation	FEP	1.53±0.05
Braid	Tinned copper	1.98±0.05
Jacket	FEP	2.5±0.05
Connector A	RP-SMA-k	
Connector B	SMA-J	
Electrical Data		
Capacitance (pF/m)	95.5	
Impedance (ohm)	50±3(at1ns@TDR)	
ConductorResistance (Ω/km)	302.OHM	
Working Frequency (GHz)	6.0	
Max. Working Voltage (Vrms)	1000	
Frequency (MHz)	**Attenuation (dB/100ft)Nom**	
50	≤7.62	
100	≤10.69	
200	≤15.04	
400	⩽21.15	
700	≤27.85	
900	≤31.51	

Copyright ©2012–2020， Chengdu Ebyte Electronic Technology Co.,Ltd.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Disclaimer

EBYTE reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of EBYTE is strictly prohibited.

The information contained herein is provided "as is" and EBYTE assumes no liability for the use of the information. No warranty, either express or implied, is given, including but not limited, with respect to the accuracy, correctness, reliability and fitness for a particular purpose of the information. This document may be revised by EBYTE at any time. For most recent documents, visit www.cdebyte.com.

About us

Sales hotline.: 4000-330-990 Company Phone: 028-61399028
Technical Support: support@cdebyte.com Official website: www.cdebyte.com
Company address: Building B5, No.199 West Avenue, Gaoxin West District, Chengdu, Sichuan Province

成都亿佰特电子科技有限公司
Chengdu Ebyte Electronic Technology Co.,Ltd.

Copyright ©2012–2020, Chengdu Ebyte Electronic Technology Co.,Ltd.

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000